RODIN®

CHROMA FLASH™

Consistent Flash Post-Curing Designed with Rodin® Materials



Stable Material Performance

Predictable Surface and Aesthetic Outcomes

Open, Material-First System

Simplified, Low-Sensitivity Workflow

Engineered to deliver consistent, reliable polymerization without nitrogen, Chroma Flash simplifies post-curing while supporting predictable mechanical properties, surface quality, and workflow outcomes.



Comparison Table	Chroma Flash	Leading competitors
Xenon Flash Curing	✓	X
Integrated Material Library	✓	X
Customizable Save Profiles	✓	X
Tack Cure Cycles	✓	X
Seamless Workflow Intergration	✓	X
Wireless Connectivity	✓	X
N2 Compatibility	✓	X

Technical Specifications

CATEGORY	SPECIFICATIONS
Inner Curing Chamber Dimension	111 x 111 x 43.5 mm
Device Dimensions	256 x 330 x 223.76 mm
LIght / Source	Xenon Flash / Stroboscopic
Wavelength	280-950 nm
Rated Voltage	110-240V
Weight	8.2 kg
Open / Close System	Open
N_2 Compatibility	Yes

DESIGN PRINT MATERIALS WASH & FINISH CURE DELIVER



Pac-Dent, Inc.
670 Endeavor Circle, Brea, CA 92821
www.rodin-3d.com | www.pac-dent.com

Ackuretta Technologies Pvt. Ltd.
2F-3, No. 56, Lane 258, Ruiguang Road
Neihu District, Taipei City 114061, Taiwan
www.ackuretta.com

Made in China